Update on the Global Precipitation Measurement (GPM) Mission

October 18, 2005



Arthur Y. Hou Arthur.y.hou@nasa.g ov


National Academies Committee Meeting on the Future of Rainfall Measuring Missions, Washington, DC



- GPM science objectives and observation context
- Evolution from TRMM to GPM
- GPM capabilities
- GPM validation
- GPM applications
- NASA-NOAA partnership opportunities



Global Water and Energy Cycle Observation Strategy



GPM

- Flagship mission for NASA's Global Water and Energy Cycle (GWEC) research and applications
- Important contribution to the U.S. Climate Change Science Program & the U.S. Weather Research Program
- Building on
 - the success of TRMM
 - NASA/JAXA capabilities in precipitation measurements from space
 - national and international partnerships in satellite constellation formation and ground validation
- Prototype for the emerging Global Earth Observing System of Systems (GEOSS), an international effort to provide comprehensive, long-term, and coordinated observations of the Earth

- Advancing precipitation measurement capability from space:
 - through combined use of active and wide-band passive remote-sensing techniques
- Advancing understanding of global water/energy cycle variability and fresh water availability:
 - through better measurement of the space-time variability of global precipitation
- Improving weather forecasting skills:
 - through more accurate and frequent measurement of instantaneous rain rates
- Improving climate modeling & prediction capabilities:
 - through better understanding of precipitation microphysics, surface water fluxes, soil moisture storage, and atmospheric latent heating distribution
- Improving prediction capabilities for floods, droughts, fresh water resources, crop conditions, & other water-related applications:
 - A science mission with integrated applications through improved temporal sampling and high-resolution spatial coverage goals



S

Ø

Σ

0

۵.

Evolution from TRMM to GPM







TRMM has demonstrated the advantages of using a precipitation radar together with a passive microwave radiometer to provide scientifically robust rainfall measurements from space.

GPM core satellite carries

- a dual-frequency radar (DPR)
- a passive microwave imager (GMI) with high-frequency capabilities

to serves as

- a precipitation physics observatory
- a calibration/training system

to refine *global* precipitation measurements from a constellation of dedicated and operational PMW radiometers.



0

Σ

œ

0

S

Ø

Σ

Z

0

0

GPM Reference Concept

OBJECTIVES

OBJECTIVES

 Understand horizontal & vertical structure of rainfall, its macro- & micro-physical nature, & its associated latent heating

 Train & calibrate retrieval algorithms for constellation radiometers Constellation

- Provide sufficient global sampling to significantly reduce uncertainties in shortterm rainfall accumulations
- Extend scientific and societal applications

Core Satellite

- TRMM-like spacecraft (NASA)
- H2-A rocket launch (TBC, JAXA)
- Non-sun-synchronous orbit
 - ~ 65° inclination
 - ~407 km altitude
- Dual frequency radar (JAXA) Ku-Ka Bands (13.6-35.5 GHz)
 - ~ 4 km horizontal resolution
 - ~250 m vertical resolution
- Multifrequency radiometer (NASA)
 10.65, 18.7, 23.8, 36.5, 89.0, 166, 183.3 GHz

Constellation Satellites

- Pre-existing operationalexperimental & dedicated satellites with PMW radiometers
- Revisit time
 - 3-hour goal at ~90% of time
- Sun-synch & non-sun-synch orbits
 600-900 km altitudes

Ground Validation Sites

- Ground measurement & calibration
- Cooperative international partners

Precipitation Processing System


Core

• Global precipitation products from input data provided by a consortium of cooperative international partners



8

0



Detection of light rain (< 0.5 mm/h) and snow requires HF (> 90 GHz) radiometer channels and greater radar sensitivity than TRMM/PR



Σ

ш

۳ 2

A S

Σ

Z

0


۵

P R E

8

Dual-Frequency Precipitation Radar


JAXA/NICT Dual Frequency (13.6, 35.55 GHz) Ku-Ka Band Precipitation Radar (DPR)





Advantages of GPM DPR over TRMM PR

- Increased sensitivity for light rain and snow detection Addition of Ka band (35.5 GHz) to Ku band (13.6 GHz) improves the detection threshold from 0.5 to 0.17 mm/h, significantly improving measurements of rain occurrences in light rain and snow events
- Better overall measurement accuracy replacing the surface reference technique for path-integrated-attenuation correction with dualfrequency methods
- More detailed microphysical information detection of drop size distribution and identification of liquid, frozen, and mixed phase precipitation to provide an improved cloud database for rain & snow retrievals for both the Core and constellation radiometers



Simulated retrievals based on synthetic noises added to Hurricane Bonnie observations and an assumed drop size distribution

Z. Haddad et al. (JPL)





ш

œ

0

Ø

Σ

0

d

•

P R E

d


8

0


Science value of HF channels on GMI


- Measurement of frozen precipitation
- · Measurement of light rain
- Improved PMW retrieval algorithms over land
- Improved precipitation measurements in mid- and high-latitudes in cold seasons

HF channels on GPM Core enabling the testing and evaluation of constellation PMW algorithms using the DPR NOAA NEXRAD Data AMSU-B 89 GHz AMSU-B 1



Radar reflectivity composite of the March 5-6, 2001 New England blizzard (75 cm of snow fell on Burlington, VT) Surface effects evident over the Great Lakes, the St. Lawrence River, and along the Atlantic coast. Cannot distinguish surface from cloud effects. Surface effects screened by water vapor. Snowfall appears over New England as low brightness temperatures





G. Skofronick-Jackson et al. (GSFC)

HF channels



Σ Œ > A Σ 0 ۵ Œ ۵ 8

Current average revisit time by PMW radiometers

TRMM, Aqua, F13, F14, F15

(< 3h over 34% of globe)

hour


Expected GPM-era average revisit time

GPM Core, GCOM-W, NASA-1, EGPM, 3 NPOESS's

(< 3h over 96% of globe)



GPM validation goes beyond direct comparisons of surface precipitation rates between ground and satellite measurements



GV goal is to provide ground observations for direct satellite product assessment and for algorithm/application improvements



8

0



- Surface precipitation statistical validation sites for direct assessment of GPM satellite data products:
 - Co-located with existing or upgraded national network (NEXRAD etc.) and dense gauge networks to identify and resolve significant discrepancies between the national network and satellite estimates
- Precipitation process sites for improving understanding and modeling of precipitation physics in physical and radiance spaces for satellite retrieval algorithm improvements:
 - Continental tropical, mid- and high-latitude sites (including orographic/coastal sites and targeted sites for resolving discrepancies between satellite algorithms)
 - Oceanic tropical and mid-latitude sites
 - Aircraft measurements
- Integrated hydrological sites for improving hydrological applications:
 - Co-located with existing watersheds maintained by other US agencies and international research programs to use hydrological basins as an integrated measure of the goodness of precipitation products

NASA NO TACA partners nipopportunities



- Σ ш œ 0 S A Σ Z 0 ۵ ш Œ 4 A 8 0
- 1. Level 1 Orbital Swath Brightness Temperatures From NASA Sensors (within 15 minutes of observation at 90% of time)
- 2. Level 2 Orbit Swath Products (similar to TRMM) and 3-Hourly Outreach Rain Maps (updated as data arrive)
- 3. Level 3 Grid Products
 - (1) 3-hourly @ 0.25 x 0.25 deg; (2) daily @ 0.25 x 0.25 deg;
 - (3) pentad @ 0.25 x 0.25 deg; (4) monthly @ 0.25 x 0.25 deg
 - Simplified & integrated parameter set:
 - (1) surface precipitation rate, (2) convective-stratiform separation, (3) latent heating profile, (4) bulk DSD parameters, (5) confidence index
 - Three types of retrieval products ordered by retrieval quality:
 - (1) core (combined DPR GMI) product, (2) constellation radiometer product, (3) microwave radiometer and sounder (e.g., AMSU, ATMS) product
- 4. Full Resolution Pixel Tables

Instantaneous rain pixels from all satellite sources within individual 3-h 0.25 x 0.25 deg grid elements

5. Level 4 Merged Satellite Microwave-IR-Gauge Products

Goal is a seamless transition of precipitation products from TRMM to GPM to maintain continuity in data records.



E

œ

o s

Ø

M E

Z

0

d

0

P R E

d

8

0


Lessons learned:


- Direct benefits of observations of precipitation intensity and structure
 - Monitoring extreme precipitation events and freshwater availability

- Improving position fix for typhoon/hurricane and interior in Nautical Miles

Higher-resolution GPM radiometer data can provide better position fixes in early stages of storm development

TMI 85GHz Image of enclosed eye with spiral bands







œ 5 Ø Σ 0 0

- Research in the pre-GPM phase is crucial for developing innovative techniques to maximize the benefits of precipitation observations in many application areas:
 - NWP, data assimilation, and reanlaysis:
 - Advanced assimilation methods to extract maximum information from precipitation data in the presence of forecast model errors
 - Improved understanding and modeling of precipitation error properties
 - Hydrological modeling & prediction:
 - Innovative hydrological modeling and prediction systems
 - Hydrometeorological testbeds for evaluating the quality of satellite precipitation products in hydrological applications
 - Improved techniques for merging high-resolution global precipitation products based on combined satellite and ground measurements



Ongoing & future GPM interactions with NOAA

- Space Hardware
- · Integration of IPO NPOESS and DMSP Satellite Series into GPM Constellation Fleet
- Weather, Climate, and Hydrological Prediction
- Coordination with <u>NOAA's</u> NCEP (e.g. HPC, CPC), National Weather Service (NWS), NESDIS, and others to understand <u>NOAA's</u> Operational Requirements for Using Precipitation Data in Model Assimilation, Short-term Forecasts/Nowcasts, Climate Prediction, River/Hydrologic Prediction, and Tropical Prediction
- Joint Center for Satellite Data Assimilation (Goddard/NCEP) activities on rainfall assimilation to enhance existing efforts to effectively assimilate existing and emerging satellite datasets into NOAA models
- Ongoing Discussions with NOAA Hydrologic Divisions on integration of GPM data into blended gauge-radar products and software.
- Science Coordination Activities
- Significant <u>NOAA</u> Participation in ongoing GPM Science Workshop Series, Working Group Report Development, and Science Implementation Plan Development
- Ad-Hoc NASA-NOAA GPM Working Group to identify and nurture GPM partners and identify funding lines in NOAA budget
- NASA-NOAA Research and Operations (R&O) Working Group to define "Global Precipitation Measurement Capability"

